# **3000+ CFM PATENTED FOCUS™ TECHNOLOGY**

# **Phoenix AAM - AXIAL AIR MOVER**

#### WITH FOCUS™ TECHNOLOGY

The Phoenix Axial Air Mover revolutionized evaporative drying by producing 3000 CFM of airflow while using less than 2.5 amps of electricity (high speed). The Phoenix Axial Air Mover is the industry's only air mover specifically engineered with patented Focus<sup>™</sup> Technology. Focus<sup>™</sup> Technology not only produces air velocities greater than competitive products, but also focuses those velocities on hard-to-dry areas such as carpet and pad, sub-floor and walls.

The Phoenix Axial Air Mover operator interface is conveniently located for easy access and features a power indicator lamp, a 3-position switch, an hour meter, a GFCI outlet, and a circuit breaker, eliminating nuisance trips to the breaker box.

# **FEATURES**

- Less than 2.5 amps on High Speed
- Power-on indicator light
- · Automatic hour meter displays site run time
- On-board power management:
- Circuit breaker protects air mover and attached devices and prevents nuisance visits to the junction box
- GFCI protection promotes operator safety in wet applications
- Duplex AC outlet allows daisy chaining of up to four axial air movers
- 20 ft AC cord with cord management
- Units interlock for ease of stacking during storage and handling
- Weighs 2.5 lbs less than competitive units
- Over 3000 CFM on high

Xactimate Code: WTRDRY+







#### 1.800.533.7533

#### **USEPHOENIX.COM**

# **3000+ CFM PATENTED FOCUS™ TECHNOLOGY**

# **Phoenix AAM - AXIAL AIR MOVER**

**SPECIFICATIONS** 

## **PART NUMBERS**

4025200 (Red) 4030680 (Blue)

## POWER

Current Draw: 2.5 Amps (High Speed) Voltage: 115 VAC, Grounded

### **DRIVE MOTOR**

1/4 hp 1-phase 110/120 VAC 2-speed 4-pole, PSC Electric motor

#### CFM

Approximately 3000 CFM

# OUTLET

15A UL Rated GFCI Duplex Receptacle

# CORD

20 ft Power Cord

### DIMENSIONS

	UNIT	SHIPPING	
WIDTH:	19.125"	19.375"	
HEIGHT	19.5"	20"	
DEPTH:	15.2"	15.5"	
WEIGHT:	29.5 lbs	32.7 lbs	

# POPULAR ACCESSORIES AND REPLACEMENT FILTERS

4025092Motor4025095Blade4021597Hour Meter4025205GFCI Duplex Outlet4025203Circuit Breaker4025460AAM Stand

run-time hour meter, GF





Units interlock for ease of stacking during storage and handling.



#### **USEPHOENIX.COM**

1.800.533.7533

# WARRANTY

Year 1 - 100% of Parts and Labor Year 2 100% Parts only (all components) Years 3-7 - Materials and workmanship of the housing only.

## PATENT

7,331,759



Innovative control panel includes power-on light, run-time hour meter, GFCI outlet and more.