

OVER 1,000 CFM AND STACKS 4 HIGH

Phoenix Stackable CAM - CENTRIFUGAL AIR MOVER

LOW AMPS, HIGH CFM, SECURELY STACKS UP TO 4 UNITS HIGH

The Phoenix Stackable CAM Pro offers all the great features of our proven CAM air movers, with the addition of an innovative stackable cabinet design. Featuring multiple contact points and interlocking side grills, the Phoenix Stackable CAM Pro can be stored safely and securely up to 4 units high, freeing up valuable space in your trucks and warehouses.

The Stackable CAM Pro features class-leading airflow and efficiency. Using a unique 1/3 horsepower motor design and proprietary blower technology, the Phoenix Stackables achieve 1050 CFM at over 2800 FPM with high static pressure, while using only 2.6 amps of electricity on high speed (2.0 amps on low speed). With its low amp draw and onboard GFCI, the Phoenix Stackable CAM Pro gives you maximum airflow on a circuit, allowing up to 4 CAMs on a standard 15 amp household circuit on high speed (or up to 6 on low speed).

FEATURES

- 2-Speed, 1/3 Horsepower Motor with automatic-reset thermal protection
 - 2.6 Amps on High Speed
 - 2.0 Amps on Low Speed
- 20% more CFM/Amp than our current industry leading CAM
- Maximum Velocity – 2800 FPM (1050 CFM)
- Balanced Exhaust Airflow
- Directional Airflow Horizontal, 45° Angle, 90° Angle
- Durable, rugged, chemical resistant housing, fan wheel, and control design.
- Operator interface conveniently located for easy access, featuring: power indicator lamp and large three-position switch.
- Phoenix exclusive Pilot Light and Sealed Switch are recessed to prevent damage.
- Ergonomic carry handle and power cord storage.
- Non-marking, anti-skid, rubber feet.
- On-board duplex GFCI outlet and circuit breaker

Xactimate Code: WTRDRY



1.800.533.7533

USEPHOENIX.COM



OVER 1,000 CFM AND STACKS 4 HIGH

Phoenix Stackable CAM - CENTRIFUGAL AIR MOVER

SPECIFICATIONS

PART NUMBERS

4030990

POWER

Current Draw: 2.6 Amps (High Speed)

Voltage: 115 VAC, Grounded

DRIVE MOTOR

1/3 hp 1-phase 110/120 VAC 2-speed

Thermal cut-off

CFM

1050 CFM

OUTLET

15A UL Rated GFCI Duplex Receptacle

CORD

20 ft Power Cord

DIMENSIONS

	UNIT	SHIPPING
WIDTH:	17.25"	17.3"
HEIGHT	20"	20"
DEPTH:	19.4"	20"
WEIGHT:	27 lbs	30 lbs

WARRANTY

Year 1 - 100% of Parts and Labor

Year 2 100% Parts only (all components)

Years 3-7 - Materials and workmanship of the housing only.



On-board GFCI outlet and circuit breaker.



Units interlock for ease of stacking during storage and handling.



Positionable horizontally, 45° or 90° to ensure thorough drying.



USEPHOENIX.COM

1.800.533.7533