# **EFFICIENT, POWERFUL XL PERFORMANCE**

### **Phoenix 250 MAX - LGR Dehumidifier**

#### HIGH TEMPERATURE, HIGH CAPACITY LGR DEHUMIDIFIER

The 250 MAX combines the latest in Phoenix technology with a lineage dating back to the original Phoenix 200. The Phoenix 200, the first dehumidifier to be described as an LGR (Low Grain Refrigerant) dehumidifier, revolutionized the restoration industry. Next Phoenix introduced the legendary 200 MAX, which has been a top seller for almost 2 decades, followed by the addition of the Phoenix 200 HT featuring excellent high-temperature performance. With the 250 MAX, Phoenix has now combined the best features of the 200 MAX and the 200 HT into one unit.

The 250 MAX out performs its competitors at all temperature conditions without bypass or the need for any adjustment during operation on the jobsite. It also is one of our the most energy efficient units in terms of pints per kilowatt-hour, even beating the beloved 200 MAX.

# **FEATURES**

- Improved water removal 145 pints/day AHAM (80°F, 60%) 31 gals/day maximum
- Improved grain depression
  The driest air from an LGR
- Multiple air filter options
  Standard 65% MERV-11, or 57% MERV-8
- Multiple ducting options
  - 12" intake, 10" layflat supply
- Less than 8.2 amps
  Removes the most pints of water per kilowatt-hour
- Stainless steel cabinet
- Internal pump with 30 feet of hose
- Five-year warranty on the sealed refrigeration system

Xactimate Code: WTRDHM>>







### SALES@USEPHOENIX.COM



# EFFICIENT, POWERFUL XL PERFORMANCE

# Phoenix 250 MAX - LGR Dehumidifier

SPECIFICATIONS

#### PART NUMBER **POPULAR ACCESSORIES** 4030010 AND REPLACEMENT FILTERS 4024969 16" x 20" x 2" Pleated Media 30% MERV-8 **POWER** 4021475 16" x 20" x 2" 2" Pleated Media 65% MERV-11 4024750 12" x 25' Intake Flex Duct Current Draw: 8.2 Amps 4024935 10" x 250' Lay-flat Duct Voltage: 120 VAC, Grounded WATER REMOVAL WARRANTY 145 PPD at 80°F/60% RH (AHAM) Year 1 - 100% of Parts and Labor Year 2-5 100% of sealed refrigeration system parts CFM 365 CFM without external ducting PATENTS PATENT PENDING FILTER Pleated 16" x 20" x 2" Media MERV-11 DUCTING OPTIONS II III B SUPPLY: 10" lav-flat INTAKE: 12" flex-duct DIMENSIONS 12" Wheels UNIT SHIPPING WIDTH: 20" 24" 40" 47" HEIGHT DEPTH: 23" 26" 119 lbs WEIGHT: 137 lbs **OPERATING RANGE** 33°F to 125°F

**REFRIGERANT CHARGE** 

2 lb, 5 oz. R-410A

1/8" Thick Skid Plate



Convenient storage for power cord and drain hose.



#### SALES@USEPHOENIX.COM

1.800.533.7533